

# Instruction Manual: Swell

## What does Swell do?

- Boat Cover tension: The inflatable design keeps your boat cover tight, so rainwater doesn't pool like a stagnant pond.
- Mold and Mildew Defense: Constant airflow keeps things breezy, combating mold and mildew from making themselves at home.
- Pest Deterrent: What do pests hate most? Minty scents, airflow, and subtle vibrations. What does Swell provide? You guessed it: Minty scents, constant airflow, and subtle vibrations. Consider pests evicted.

## Installation & Use

No tools needed: Swell comes pre-assembled.

### Quick Start Instructions:

1. Put Swell in your boat with your boat cover installed.

**\*\*DO NOT CONNECT/TIGHTEN COVER STRAPS UNTILL SWELL IS FULLY INFLATED\*\***

2. Pull a few feet of fabric out to ease inflation.
3. Plug it in and adjust if needed.
4. Toss the Scent Booster in your boat.
5. Fire up the grill and cook a ribeye, you earned it. Good job.

### Detailed Instructions:

Go ahead and get your boat cover installed on your boat.

#### Step 1: DO NOT OPEN THE LID!

Just kidding, we know you already did. Congratulations, you nailed Step 1. Heck yeah, we're off to a good start.

#### Step 2: Check the Packet

The packet that includes these instructions has a few key items inside.

1. A Ball Magnet
  2. A Captain-head Scent Booster (air freshener)
- Set those aside for now, we'll come back shortly

#### Step 3: Power Cord Prep

Grab the power cord and controller assembly from the box. It's pre-attached so don't play tug-of-war with it. Just get the slack of the cord out of the box.

#### Tip: Swell won't power on?

Check the quick-release safety connectors on the power cord, **there are 2**. They're designed to prevent damage from accidental tugs. One is easily visible 3 ft from the controller, the other is located underneath the inflatable fabric, close to the fan. Open a zipper to access.



**\*DO NOT YANK ON THE FABRIC.** The inflatable portion is packed, folded, and pre attached in the box. No need to break things; we're only on Step 3. Geez.

#### Step 4: Pull out some fabric

**Gently** pull a few feet of fabric from Swell's base. Locate the magnet attached to the fabric. That is the top/center of the inflatable. That little guy will come in handy soon.

#### Step 5: Position Swell in the Boat

Place Swell under your boat cover and keep it within reach for now. Pull out another foot of fabric and let the power cord/controller assembly hang over the gunwale (that's the "edge").

#### Step 6: Connect the Magnets

Remember the ball magnet from Step 2? Grab it.

- Place the ball magnet on top of your boat cover.
- Lift the magnet attached to the fabric (from Step 4) under the cover and let the two connect. Enjoy that click.

#### Step 7: Center Swell

Get Swell as centered as possible on your boat deck. Those magnets should line up nicely over the cabin. If you don't feel like climbing in, use a pole to nudge Swell into place (maybe that old extension pole you just replaced...)

#### Step 8: Power on

Alright, Here goes nothing...Grab that extension cord and Plug it in.

- **Pro Tip:** Make sure your boat cover straps are loose until Swell fully inflates.

#### Step 9: Adjust

Use the knob on the controller to adjust airflow.

Swell has 6 zipper vents around its circumference. These control airflow and how rigid Swell gets, or how easily it molds around your boat seats.

- o Start at full power with a few vents partially open.
- o Once inflated, lower power to ~50% and adjust the vents further. Many people settle at ~30% power.

#### Step 10: Add the Scent Booster (Final Step)

Remember the Captain-head air freshener from Step 2? Tie the Scent Booster string through the eyehole on one of Swell's zipper tabs, remove the plastic protector, and take a whiff. That's victory.

